



WHELAN
THE BOILING WATER SPECIALISTS

TIMERBOIL T105
For Details Contact
WHELAN INDUSTRIES
03 9560 9333
sales@whelanind.com.au

WHELAN
THE BOILING WATER SPECIALISTS

**Wall Mounted
Boiling Water Units**



WHELAN WALL MOUNTED BOILING WATER UNITS

Since the invention of the SL Series, the first patented wall mounted electrical boiling water unit in the early 1960's, Whelan Industries has earned renown for manufacturing durable and low maintenance boiling water units. It is not unusual to see quite a number of the SL Series boiling water units installed in different sectors still running after 30 years.

Each model of the Whelan range of boiling water units, wall-mounted or under-bench, has been purposely built with its own unique characteristics to satisfy different requirements of the end user, and our motto of simplicity, reliability, durability and low maintenance has set Whelan products apart from the others - we are proud to carry the name of 'Boiling Water Specialists'.

WHELAN TIMERBOIL

A wall mounted system which incorporates electronic temperature control and a 24-hour 7-day programmable timer with 28 separate on/off programs for maximum versatility and the most accurate clock in the market.

Once programmed, the ability to switch off automatically during non working hours allows you to save running costs without sacrificing the convenience of having instant boiling water ready whenever you need it. The savings from your energy bill will eventually pay off the investment of installing this boiling water system in a matter of years.

Timerboil comes in 10 different sizes, ranging from 2.5 – 60 litres in capacity.



Selection Chart Whelan Timerboil

To select the correct size unit for your needs simply determine the maximum number of cups of boiling water required at any one time, then choose the corresponding model from the chart below.

MODEL NO.	No. OF CUPS SERVED	CUP/Hr RECOVERY	TOTAL KW	PHASE	VOLTAGE	HEIGHT mm	WIDTH mm	DEPTH mm
TID 2.5	13	110	2.4	1	1/240	470	330	160
TID 5	25	110	2.4	1	1/240	470	330	160
TI 7.5	38	110	2.4	1	1/240	580	430	180
TI 10	50	110	2.4	1	1/240	580	430	180
TI 15	75	110	2.4	1	1/240	650	450	260
TI 20	100	135	3.0	1	1/240	650	450	260
		220	4.8	2	2/240			
		320	7.2	3	3/240			
TI 25	125	135	3.0	1	1/240	750	460	260
		220	4.8	2	2/240			
		320	7.2	3	3/240			
TI 30	150	135	3.0	1	1/240	750	460	260
		220	4.8	2	2/240			
		320	7.2	3	3/240			
* TI 50*	250	320	7.2	3	3/240	800	600	260
* TI 60*	300	320	7.2	3	3/240	800	600	260

* Models TI 50 and TI 60 will be supplied in white colourbond as standard. Optional stainless steel casing can be supplied as specified

WHELAN DYNAMICBOIL SL SERIES

The SL Series is the only unit in world where incoming water is boiled in the heating chamber before it enters into the storage chamber to be dispensed. This means that the incoming cold water is not mixed with stored boiling water within the unit; you'll only get boiling water when you turn on the tap or you'll get no water at all. It also boasts the biggest capacity available in the market, the largest in this range will deliver up to 450 litres (2250cups) of boiling water continuously.

Another unique feature of the SL Series, is the ability to be connected to a 10amp power point for units up to 90 litres in capacity. This model is normally custom built to suit each client's configuration, such as placement of the water inlet and electrical service can be on the left or right, bottom or top of unit, and overflow pipe on the left or right bottom of the unit.

Dynamicboil SL Series comes in 15 different sizes, ranging from 2.5 – 450 litres in capacity.



Selection Chart Whelan Dynamicboil SL Series

To select the correct size unit for your needs simply determine the maximum number of cups of boiling water required at any one time, then choose the corresponding model from the chart below.

MODEL NO.	No. OF CUPS SERVED	CUP/Hr RECOVERY	TOTAL KW	PHASES/ VOLTAGE	HEIGHT mm	WIDTH mm	DEPTH mm	OVERFLOW
SL.2.5	13	70	1.58	1/240	430	460	185	3/4" BSP
SL.5	25	70	1.58	1/240	500	460	185	3/4" BSP
SL.7.5	38	70	1.58	1/240	550	460	185	3/4" BSP
SL10	50	100	2.25	1/240	500	600	250	3/4" BSP
SL.15	75	100	2.25	1/240	550	600	250	3/4" BSP
		210	4.75	2/240				
SL.20	100	100	2.25	1/240	550	600	250	3/4" BSP
		210	4.75	2/240				
SL.25	125	100	2.25	1/240	650	600	250	3/4" BSP
		210	4.75	2/240				
SL.30	150	100	2.25	1/240	700	600	250	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
SL.50	250	100	2.35	1/240	900	600	250	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
SL.60	300	100	2.35	1/240	1000	600	250	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
BW 90	450	100	2.50	1/240	950	600	510	3/4" BSP
		230	4.8	2/240				
		340	7.2	3/240				
BW 136	680	230	4.8	2/240	950	740	635	3/4" BSP
		340	7.2	3/240				
BW 180	900	230	4.8	2/240	950	800	700	3/4" BSP
		340	7.2	3/240				
BW 225	1125	340	7.2	3/240	950	900	800	3/4" BSP
BW 450	2250	340	7.2	3/240	1200	1020	915	11/2" BSP

Specifications subject to change without notice. 1 litre equals 5 cups approximately

SL Series will be supplied in white colourbond as standard. Optional stainless steel casing can be supplied as specified

WHELAN ECONOBOIL & THERMOBOIL

A basic, no frills wall mounted boiling water system that provides boiling water efficiently.

The Econoboil & Thermoboil ranges use thermostat technology to control the water temperature. Combined with a manual reset and over temperature cut-out switch, your unit will be steam free.

Econoboil comes in 2.5 & 5 litres, ECD2.5 & ECD5

Thermoboil comes in 8 different sizes ranging from 7.5 – 60 litres in capacity.



Selection Chart Whelan Econoboil & Thermoboil

To select the correct size unit for your needs simply determine the maximum number of cups of boiling water required at any one time, then choose the corresponding model from the chart below.

MODEL NO.	No. OF CUPS SERVED	CUP/Hr RECOVERY	TOTAL KW	PHASE	VOLTAGE	HEIGHT mm	WIDTH mm	DEPTH mm
ECD 2.5	13	80	1.8	1	1/240	355	270	160
ECD 5	25	110	2.4	1	1/240	470	330	160
TH 7.5	38	110	2.4	1	1/240	580	450	180
TH 10	50	110	2.4	1	1/240	580	450	180
TH 15	75	110	2.4	1	1/240	650	460	260
TH 20	100	135	3.0	1	1/240	650	460	260
		220	4.8	2	2/240			
		320	7.2	3	3/240			
TH 25	125	135	3.0	1	1/240	750	460	260
		220	4.8	2	2/240			
		320	7.2	3	3/240			
TH 30	150	135	3.0	1	1/240	750	460	260
		220	4.8	2	2/240			
		320	7.2	3	3/240			
* TH 50*	350	320	7.2	3	3/240	750	600	260
* TH 60*	300	320	7.2	3	3/240	800	600	260

* Models TH 50 and TH 60 will be supplied in white colourbond as standard. Optional stainless steel casing can be supplied as specified



Whelan Industries
Factory 1, 214-224 Wellington Road
Mulgrave, VIC, 3170

Phone: 03 9560 9000
Fax: 03 9560 2233
Email: sales@whelanindustries.com.au
www.whelanindustries.com.au

Postal Address:
PO Box 48
Mount Waverley, VIC, 3149